



EC-TYPE EXAMINATION CERTIFICATE



The following model of Personal Protective Equipment has been subjected to an EC-type examination in accordance with the article 10 of the PPE Directive (89/686/EEC) and has been shown to satisfy the relevant provisions of the Directive.

Certificate N° 0075/2648/162/12/17/1800

Issued by CTC, Notified Body N°0075, to the following model of personal protective equipment :

Manufacturer : QINGDAO HANDDIER SAFETY GLOVES CO.,LTD
MAJIA VILLAGE JIAOXI TOWN ,JIAOZHOU CITY ,QINGDAO ,CHINA

CHINA

Distributor : /

Description

PPE Type : *protective glove against mechanical risks*

Product reference : LA507

Glove description : 10 GAUGE POLYCOTTON LINER, CRINKLE LATEX PALM COATING

This product is a category II.


Available sizes : 8 9 10

Pictures :



EN 388

LA507



2122X

EN420

SIZE :10

Reference standard :

Levels of performance / class of protection

EN 420:2003+A1:2009

EN 388:2016

2 1 2 2 X

The levels of performance have been measured on the palm

« X » means that the test hasn't been performed ; no protection is required

At the date of certificate the product is in compliance with Annex XVII of REACh regulation (n° 1907/2006 and revisions)


Full description of the PPE, reference rules verified in the context of the EC-type examination and information given on the product are detailed in the manufacturer's technical file index 01 dated from DECEMBER 2017

NOTA : Any modification to new items of the personal protective equipment object of this CE type approval certificate or any modification of the information contained in the manufacturer technical file which served for the deliverance of the CE type approval certificate (change of adress, change of company status) should be brought to the attention of the notified body in accordance with law n° R.4313-38 of the French Code of Work

Issued in Lyon by

Date of issue : December 1st, 2017

Lionel Gaudillere
PPE certification manager



www.ctcgroupe.com

cemarking@ctcgroupe.com



In application of the Directive 89/686/EEC of the 21st December 1989, concerning the alignment of member states legislation relating to personal protective equipment and in application of relevant requirements of the french labor code, providing by the transcription of these Directive into french regulation.

CTC - 4, rue Hermann Frenkel - 69367 Lyon cedex 07 - France
Tél : +33 (0)4 72 76 10 10 - Fax : +33 (0)4 72 76 10 00 - ctclyon@ctcgroupe.com

Comité Professionnel de Développement Économique (CPDE) Cuir Chaussure Maroquinerie Ganterie
Loi 78-854 du 22.06.1978 - Siret 77564972600160 - Code NAF 9412Z - TVA FR 98775649726

QINGDAO HANDDIER SAFETY GLOVES CO.,LTD

MANUFACTURER'S TECHNICAL FILE

Reference of the product	:	LA507
Technical file index	:	01
Last update	:	DECEMBER 2017

IDENTIFICATION

Reference of the product :	:	LA507
Basic model		
Technical file index :	:	01
Last update :	:	DECEMBER 2017

Manufacturer :

QINGDAO HANDDIER SAFETY GLOVES CO.,LTD

MAJIA VILLAGE JIAOXI TOWN ,JIAOZHOU CITY ,QINGDAO ,CHINA

CHINA

tel : 0532-80988338

fax : 0532-80988339

Factory :

QINGDAO HANDDIER SAFETY GLOVES CO.,LTD

MAJIA VILLAGE JIAOXI TOWN ,JIAOZHOU CITY ,QINGDAO ,CHINA

CHINA

tel: 0532-80988338

fax: 0532-80988339

GLOVE DESCRIPTION

Glove description :

10 GAUGE POLYCOTTON LINER, CRINKLE LATEX PALM COATING

type of coating finish : crinkle

Visual description :



Field of use, Risks against which the product protects :

Mechanical risk

Available sizes :

Minimum length of glove (mm)	Sizes
240	8
250	9
260	10

Glove constitution :

	Reference	Color	Material	Surfacic mass	Gauges	Thickness
Palm		Black	latex	420g/m2		1mm
		Yellow	polyester/cotton	300g/m2	10	
Back		Yellow	polyester/cotton	300g/m2	10	
Cuff		Yellow	polyester/cotton/elastic	330g/m2	10	
Binding		Black	polyester			

PROTECTION SCOPE

This glove meets the essential requirements of the Personal Protection Equipment Directive (89/686/CE).

This glove is designed for mechanical risks.
It is a category II product.

GENERAL REQUIREMENTS

Standard EN 420 : 2003 + A1 : 2009

Dexterity : 4
PH of glove and lining is greater than 3.5 and lower than 9.5 : yes
Chromium VI lower than the detection limit : conform
Size : conform

At the date of certificate the product is in compliance with Annex XVII of REACH regulation (n° 1907/2006 and revisions)

SPECIFIC REQUIREMENTS AND PERFORMANCE LEVELS

Mechanical hazard EN 388 : 2016

Protection offered	Performance levels
Abrasion resistance	2
Blade cut resistance	1
Tear strength resistance	2
Puncture resistance	2
Cut Resistance method (EN ISO 13997)	X
Impact Protection	-

The levels of performance have been measured on the palm
« X » means that the test hasn't been performed ; no protection is required

TEST REPORTS

Laboratory	CTC	Other
EN 420	S170100296_2 S170912498_1	
Azo	S170100296_2 S170912498_1	
EN 388	S170912498_1	
OTHER	S170100318_2(DMFU) S170912498_1(TIN CAD PAHS)	

MARKING - PACKAGING

Information printed on the glove :

Logo of the authorized representative :

Logo 

Glove's reference : LA507

Size indicator

Pictograms related to risks against which protection is offered with performance levels

Information pictogram

Marking example :



Method of marking on the glove :

silk printing

Packaging :

12pairs/ polybag , 240 pairs / carton

MEANS OF CONTROL

1. the supply of material: use high grade yarn in the market, excellent latex coated, dye matter of free AZO
2. we will exam to see the smoothness and flatness of th gloves's surface, next step is viscosity tests and length test, very strict so that we can ensure the quality.
3. the technology of producing the skilled employee and engineers rich of innovation, no stopping of perfecting technics.

INSTRUCTION FOR USE

QINGDAO HANDDIER SAFETY GLOVES CO.,LTD

MAJIA VILLAGE JIAOXI TOWN ,JIAOZHOU CITY ,QINGDAO ,CHINA

CHINA

Glove reference : LA507

Available sizes : 8 9 10

Glove description :

10 GAUGE POLYCOTTON LINER, CRINKLE LATEX PALM COATING

THIS GLOVE IS A PERSONAL PROTECTIVE EQUIPMENT BELONGING TO THE CATEGORY II.

It meets the requirements of the Directive 89/686/CEE : innocuousness, comfort, solidity.

It has been subject to a CE type Examination performed by :

C.T.C. (0075)
4, rue Hermann Frenkel
69367 LYON Cedex 07
FRANCE


Applicable standards :

The glove meets the requirements of the standard EN 420 « General requirements for work glove ». Dexterity : 4

Moreover, this glove has been designed for the following applications :

Application :

Mechanical hazard - EN 388



2 1 2 2 X

Levels of performance

Abrasion resistance	2	(on 4 maxi)
Blade cut resistance	1	(on 5 maxi)
Tear resistance	2	(on 4 maxi)
Puncture resistance	2	(on 4 maxi)
Cut Resistance method (EN ISO 13997)	X	(A to F)
Impact Protection		

« X » means that the test hasn't been performed ; no protection is required

Protection limit :

This model does not contain any substances at levels that are known to, or suspected to, adversely affect user hygiene or health.

The protection against risks or hazards which are not mentioned in this document is not warranted. The levels of performance mentioned are only valid for the palm of the glove. The levels of performance mentioned are only valid for new gloves, not washed, nor regenerated. These levels of performance are obtained from the tests done according to conditions defined by the applicable standards.

This glove shall not be in contact with fire.

Users should be warned that gloves should not be worn when there is a risk of entanglement by moving parts of machines.

Storage and cleaning notice

Keep in its original packaging, under ordinary temperature and humidity conditions and in clean, covered and ventilated premises.