

QINGDAO HANDDIER SAFETY GLOVES CO.,LTD

**MANUFACTURER'S TECHNICAL FILE TO THE
PPE REGULATION 2016/425**

Reference of the product	:	HNLC809
Article code	:	/
Technical file index	:	01
Last update	:	JANUARY 2022

IDENTIFICATION

Reference of the product :	:	HNLC809
Article code :	:	/
Basic Model		
Technical file index :	:	01
Last update :	:	JANUARY 2022

Manufacturer :

QINGDAO HANDDIER SAFETY GLOVES CO.,LTD

MAJIA VILLAGE JIAOXI TOWN,JIAOZHOU CITY,QINGDAO,266555

CHINA

tel : +86 18561501136

Factory :

QINGDAO HANDDIER SAFETY GLOVES CO.,LTD

MAJIA VILLAGE JIAOXI TOWN,JIAOZHOU CITY,QINGDAO,266555

CHINA

tel: +86 18561501136

fax: N/A

GLOVE DESCRIPTION

General glove description and intended use:

13 gauge HPPE (high performance polyethylene)/ steel wire/ fiber glass liner with nitrile sandy palm coated gloves

This glove is designed against mechanical risks.

Type of coating finish : sandy

Visual description (picture back and palm sides) :



Risk assessment (Essential Health and Safety Requirement. Annex II - PPE Regulation)			
		Applicable	Covered by
§1	Requirements defined in the Annex II §1 are applicable to all PPE	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/> Standard <input checked="" type="checkbox"/> Instruction for use <input checked="" type="checkbox"/> Marking
§1.4	Manufacturer's instructions and information is available	<input checked="" type="checkbox"/>	<input type="checkbox"/> Standard <input checked="" type="checkbox"/> Instruction for use <input type="checkbox"/> Marking
§2.5	PPE which may be caught up during use	<input checked="" type="checkbox"/>	<input type="checkbox"/> Standard <input checked="" type="checkbox"/> Instruction for use <input type="checkbox"/> Marking
§2.12	PPE bearing one or more identification markings or indicators directly or indirectly relating to health and safety	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/> Standard <input checked="" type="checkbox"/> Instruction for use <input checked="" type="checkbox"/> Marking
§3.3	The PPE is intended to protect against mechanical injuries	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/> Standard <input checked="" type="checkbox"/> Instruction for use <input checked="" type="checkbox"/> Marking

Glove constitution :

	Reference	Color	Material	Surfacic mass (g/m ²)	Gauges	Thickness
Palm		black	nitrile			1mm
		white/black	HPPE(high performance polyethylene)/steel wire/fiber glass	350g/m ²	13G	
Back		white/black	HPPE(high performance polyethylene)/steel wire/fiber glass	350g/m ²	13G	
Cuff		white/black	HPPE(high performance polyethylene)/steel wire/fiber glass/elastic	400g/m ²	13G	
Binding		red,green, black	polyester			

PROTECTION SCOPE

This glove meets the essential requirements of the Personal Protective Equipment Regulation 2016/425.

This glove is designed against mechanical risks.
It is a category II product.

GENERAL REQUIREMENTS

Standard EN ISO 21420 : 2020

Dexterity : 5
Available size range: 7-11

The hand sizing system is based on hand circumference and hand length as defined in EN ISO 21420 Annex B table B.1

SPECIFIC REQUIREMENTS AND PERFORMANCE LEVELS

« X » indicates that the glove has not been submitted to the test or the test method appears not to be suitable for the glove design or material.

« 0 » indicates that the glove falls below the minimum performance level for the individual hazard.

Mechanical hazard EN 388 : 2016 + A1 : 2018

Protection offered	Performance levels
Abrasion resistance	4
Blade cut resistance	3
Tear strength resistance	4
Puncture resistance	3
Cut Resistance method (EN ISO 13997)	D
Impact Protection	-

The levels of performance have been measured on the palm.


TEST REPORTS

Laboratory	CTC	Other
EN ISO 21420 + innocuousness	S210605432_2 S201111731_1(DMFu) S210201074_1 S200908873_1	
EN 388	S210605432_2	

MARKING - PACKAGING

Information printed on the glove :

Logo of Manufacturer :

Logo 

Glove's reference : HNLC809

Article Code : /

Size indicator

Pictograms related to risks against which protection is offered with performance levels

Information pictogram

Address of Manufacturer :

Date of Manufacture (month/year) and/or serial/batch number :

Date of obsolescence (month/year) if applicable:

Marking example :



Method of marking on the glove :

silk screen printing/hot thermal transfer printing on back

Packaging suitable for transport:

12pairs per bag, 144pairs per carton

PPE subject to ageing :

The design performance can not be significantly affect by ageing when stored in appropriate conditions (humidity, temperature, clean , ventilated, light).

Cleaning instructions:

The gloves are not washable.

MEANS OF CONTROL

We make all inspection based on the acceptance sampling. Materials conduct inspection on all incoming raw materials and accessory materials. Conduct size checking on all component parts. Conduct visual inspection on defective parts. Checking missing parts before sending the sewers. Inspected for defects, gauged for proper thickness. Quality checking on sewing in areas of appearance, sizing (based on the EN ISO 21420 sizing standard), weight, labelling, stitches, seaming and component positioning. After coating we will make the sizing, weight, smell, PH, chemic test and cutting, abrasion test (based on EN388 standard) every one year. Finished products perform random checking (acceptance sampling) before shipment.

INSTRUCTION FOR USE

QINGDAO HANDDIER SAFETY GLOVES CO.,LTD
MAJIA VILLAGE JIAOXI TOWN,JIAOZHOU CITY,QINGDAO,266555
CHINA

Glove reference : HNLC809
Article code: /
User notice index : 01
Last update : JANUARY 2022



Glove description :

13 gauge HPPE (high performance polyethylene)/ steel wire/ fiber glass linner with nitrile sandy palm coated gloves

This glove is a personal protective equipment belonging to the category II.

It meets the requirements of the PPE Regulation 2016/425 : innocuousness, comfort, solidity.

It has been subject to a UE-type Examination performed by :

C.T.C. (0075)
4, rue Hermann Frenkel
69367 LYON Cedex 07
FRANCE

Applicable standards :

The glove meets the requirements of the standard EN ISO 21420:2020 « Protective Gloves - General requirements and test methods ».

Dexterity: 5

Available size range: 7-11

The hand sizing system is based on hand circumference and hand length as defined in EN ISO 21420 Annex B.

Moreover, this glove has been designed for the following applications :

« X » indicates that the glove has not been submitted to the test or the test method appears not to be suitable for the glove design or material.

« 0 » indicates that the glove falls below the minimum performance level for the individual hazard.

Application :

Mechanical hazard - EN
388:2016 + A1:2018



Read carefully the instructions for use provided with the product



4 3 4 3 D

Levels of performance

Abrasion resistance	4	(on 4 maxi)
Blade cut resistance	3	(on 5 maxi)
Tear resistance	4	(on 4 maxi)
Puncture resistance	3	(on 4 maxi)
Cut Resistance method (EN ISO 13997)	D	(A to F)
Impact Protection		

Protection limit :

Users should be warned that gloves should not be worn when there is a risk of entanglement by moving parts of machines.

This model does not contain any substances at levels that are known to, or suspected to, adversely affect user hygiene or health.

The protection against risks or hazards which are not mentioned in this document is not warranted.

These levels of performance are obtained from the tests done according to conditions defined by the applicable standards.

The levels of performance mentioned are only valid for new gloves, not washed, nor regenerated.

Before use, the glove shall be visually inspected for any defect or imperfections. In case of deterioration, the gloves must be scrapped (abrasion, cut, tear, ...).

No flame protection is claimed. This glove shall not be in contact with naked flame.

For gloves with two or more layers the overall classification does not necessarily reflect the performance of the outermost layer.

The levels of performance against mechanical risks are only valid for the palm of the glove.

Storage and cleaning notice

Keep in its original packaging, under ordinary temperature and humidity conditions and in clean, covered and ventilated premises.

The gloves are not washable.

PPE subject to ageing :

The design performance can not be significantly affect by ageing when stored in appropriate conditions (humidity, temperature, clean , ventilated, light).

Declaration of conformity :

Available with product.