



# EU-TYPE EXAMINATION CERTIFICATE



The following model of Personal Protective Equipment has been subjected to an EU-type examination in accordance with the module B of the PPE regulation (2016/425) and has been shown to satisfy to essential health and safety requirements.

**Certificate N° 0075/2648/162/10/19/3075**

Issued by CTC, Notified Body N°0075, to the following model of personal protective equipment :

**Manufacturer :** **Qingdao Handdier Safety Gloves Co.,Ltd**  
Majia village, Jiaoxi town Jiaozhou city Qingdao 266555  
China

### Description

**PPE Type :** *protective glove against mechanical risks*

**Product reference :** **LA631**

**Article code :** /

**Glove description :** **10 GAUGES POLYESTER TERRY LINER WITH LATEX COATED CRINKLE SURFACE GLOVES**

**Available sizes :** **9 10 11**

**Pictures :**



EN388: 2016



1 1 4 2 X



size 10  
2019/07



LA631

Majia village, Jiaoxi town Jiaozhou  
city Qingdao 266555 China

**Reference standard :**

**Levels of performance / class of protection**

**EN 420:2003+A1:2009**

-

**EN 388:2016**

**1 1 4 2 X**

« X » indicates that the glove has not been submitted to the test or the test method appears not to be suitable for the glove design or material.

At the date of certificate the product is in compliance with Annex XVII of REACH regulation (n° 1907/2006 and revisions)

Full description of the PPE, reference rules verified in the context of the EU-type examination and information given on the product are detailed in the manufacturer's technical file and the Instruction for use index 01 dated from OCTOBER 2019

NOTA : Any modification to new items of the personal protective equipment object of this EU type approval certificate or any modification of the information contained in the manufacturer technical file which served for the deliverance of the EU type approval certificate (change of address, change of company status) should be brought to the attention of the notified body in accordance with Annex V §7.2 of Regulation 2016/425.

**Issued in Lyon by**  
**Didier GUISSADO**  
Certification and Quality Manager

**Date of first issue :** 18 October 2019  
**End of validity date :** 18 October 2024



Original CTC



In application of the Regulation 2016/425 of the European parliament and the Council of 9th March 2016 related to Personal Protective Equipment and repealing the Directive 89/686/EEC.

[www.ctcgroupe.com](http://www.ctcgroupe.com)

[cemarking@ctcgroupe.com](mailto:cemarking@ctcgroupe.com)

CTC - 4, rue Hermann Frenkel - 69367 Lyon cedex 07 - France  
Tél. : +33 (0)4 72 76 10 10 - Fax : +33 (0)4 72 76 10 00 - [ctclyon@ctcgroupe.com](mailto:ctclyon@ctcgroupe.com)

Comité Professionnel de Développement Économique (CPDE) Cuir Chaussure Maroquinerie Ganterie  
Loi 78-654 du 22.06.1978 - Siret 77564972600160 - Code NAF 9412Z - TVA FR 88775649726

**Qingdao Handdier Safety Gloves Co.,Ltd**

**MANUFACTURER'S TECHNICAL FILE TO THE  
PPE REGULATION 2016/425**

<b>Reference of the product</b>	<b>:</b>	<b>LA631</b>
<b>Article code</b>	<b>:</b>	<b>/</b>
<b>Technical file index</b>	<b>:</b>	<b>01</b>
<b>Last update</b>	<b>:</b>	<b>OCTOBER 2019</b>

## IDENTIFICATION

Reference of the product :	:	LA631
Article code :	:	/
Basic Model		
Technical file index :	:	01
Last update :	:	OCTOBER 2019

### **Manufacturer :**

Qingdao Handdier Safety Gloves Co.,Ltd  
Majia village, Jiaoxi town Jiaozhou city Qingdao 266555  
China  
tel : +86 532 8694 3214  
fax : +86 532 8694 3214

### **Factory :**

Qingdao Handdier Safety Gloves Co.,Ltd  
Majia village, Jiaoxi town Jiaozhou city Qingdao 266555  
China  
tel: +86 532 8694 3214  
fax: +86 532 8694 3214

## GLOVE DESCRIPTION

### **General glove description :**

10 GAUGES POLYESTER TERRY LINER WITH LATEX COATED CRINKLE SURFACE GLOVES  
 type of coating finish : crinkle

### **Visual description (picture back and palm sides) :**



### **Field of use**

workshop, Automobile manufacturing, construction site, garden

Risk assessment (Essential Health and Safety Requirement. Annex II - PPE Regulation)			
		Applicable	Covered by
§1	Requirements defined in the Annex II §1 are applicable to all PPE	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/> Standard <input checked="" type="checkbox"/> Instruction for use <input checked="" type="checkbox"/> Marking
§1.4	Manufacturer's instructions and information is available	<input checked="" type="checkbox"/>	<input type="checkbox"/> Standard <input checked="" type="checkbox"/> Instruction for use <input type="checkbox"/> Marking
§2.5	PPE which may be caught up during use	<input checked="" type="checkbox"/>	<input type="checkbox"/> Standard <input checked="" type="checkbox"/> Instruction for use <input type="checkbox"/> Marking
§2.12	PPE bearing one or more identification markings or indicators directly or indirectly relating to health and safety	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/> Standard <input checked="" type="checkbox"/> Instruction for use <input checked="" type="checkbox"/> Marking
§3.3	The PPE is intended to protect against mechanical injuries	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/> Standard <input checked="" type="checkbox"/> Instruction for use <input checked="" type="checkbox"/> Marking

### **Available sizes :**

Minimum length of glove (mm)	Sizes
250	9
260	10
270	11

## **Glove constitution :**

	Reference	Color	Material	Surfacic mass	Gauges	Thickness
Palm	LA631-08	orange	terry-polyester	200g/m <sup>2</sup>	10 gauges	
	LA631-08	black	crinkle surface latex			2mm
Back	LA631-09	orange	terry-polyester	200g/m <sup>2</sup>	10 gauges	
Cuff	LA631-10	orange/ white	terry-polyester with elastic	250g/m <sup>2</sup>	10 gauges	
Binding	LA631-11	yellow	polyester			

## **PROTECTION SCOPE**

This glove meets the essential requirements of the Personal Protective Equipment Regulation 2016/425.  
This glove is designed for against mechanical risks.  
It is a category II product.

## **GENERAL REQUIREMENTS**

### **Standard EN 420 : 2003 + A1 : 2009**

Dexterity : 5

Size : conform

At the date of certificate the product is in compliance with Annex XVII of REACh regulation (n° 1907/2006 and revisions)

## **SPECIFIC REQUIREMENTS AND PERFORMANCE LEVELS**

### **Mechanical hazard EN 388 : 2016**

<b>Protection offered</b>	<b>Performance levels</b>
Abrasion resistance	1
Blade cut resistance	1
Tear strength resistance	4
Puncture resistance	2
Cut Resistance method (EN ISO 13997)	X
Impact Protection	-

The levels of performance have been measured on the palm

« X » indicates that the glove has not been submitted to the test or the test method appears not to be suitable for the glove design or material.


## TEST REPORTS

Laboratory	CTC	Other
EN 420 + innocuousness	D190611902_2 D190405697_2	
EN 388	D190611902_2	

## MARKING - PACKAGING

### Information printed on the glove :

Logo of Manufacturer :

Logo 

Glove's reference : LA631

Article Code : /

Size indicator

Pictograms related to risks against which protection is offered with performance levels

Information pictogram

Address of Manufacturer :

Date of Manufacture (month/year) and/or Serial number :

### Marking example :



### Method of marking on the glove :

Printed on glove

### Packaging :

12 pairs in a per bag, 120 pairs in a carton

### PPE subject to ageing :

The design performance can not be significantly affect by ageing when stored in appropriate conditions (humidity, temperature, clean , ventilated, light).

### Declaration of conformity :

Available on : [www.handdier-safety.com](http://www.handdier-safety.com)

## MEANS OF CONTROL

1. We choose the good suppliers to provide us material with good quality. At the same time, when we received the raw materials we should test some items according to relevant standard, such as EN 420 and relevant EU regulation; the bad material cannot meet requirement will be rejected.
2. when we received the raw materials for mass production, the material QC will check them serious in order that no any problem at the beginning;
3. Make samples before production, make sure samples meet the requirement of client and we test the glove as the requirment EN388 michanical risk ,EN420,and other chemical items,then start to produce; it's very important for us;
4. Regularly check the quality of products in the whole process; any unacceptable defects are found, the gloves will be discarded; QC for each step will perform inspection in accordance with our requirement strictly;
5. Confirm packing specification before packing and regularly check and keep records;
6. According to QA inspection procedures, QA will perform final inspection on some cartons of glove randomly. Then the goods can be shipped in case no any problems.
7. When do bulk production, we shall pick up some gloves from each batch to test abrasion resistance and blade cut resistance of EN 388:2016 and PAHs of latex to control the quality.

## INSTRUCTION FOR USE

### Qingdao Handdier Safety Gloves Co.,Ltd

Majia village, Jiaoxi town Jiaozhou city Qingdao 266555  
China

Glove reference : LA631

Article code: /

User notice index : 01

Last Update : OCTOBER 2019

Available sizes : 9 10 11

EN388: 2016



1 1 4 2 X



size 10  
2019/07



LA631

Majia village, Jiaoxi town Jiaozhou  
city Qingdao 266555 China

### Glove description :

10 GAUGES POLYESTER TERRY LINER WITH LATEX COATED CRINKLE SURFACE  
GLOVES

THIS GLOVE IS A PERSONAL PROTECTIVE EQUIPMENT BELONGING TO THE CATEGORY II.

It meets the requirements of the PPE Regulation 2016/425 applicable from April 21th, 2018 : innocuousness, comfort, solidity.

It has been subject to a UE-type Examination performed by :

C.T.C. (OO75)  
4, rue Hermann Frenkel  
69367 LYON Cedex 07  
FRANCE

### Applicable standards :

The glove meets the requirements of the standard EN 420 : 2003 + A1 : 2009 « General requirements for work glove ». Dexterity : 5

Moreover, this glove has been designed for the following applications :

#### Application :

Mechanical hazard - EN 388 : 2016



1 1 4 2 X

Levels of performance

Abrasion resistance	1	(on 4 maxi)
Blade cut resistance	1	(on 5 maxi)
Tear resistance	4	(on 4 maxi)
Puncture resistance	2	(on 4 maxi)
Cut Resistance method (EN ISO 13997)	X	(A to F)
Impact Protection		

« X » indicates that the glove has not been submitted to the test or the test method appears not to be suitable for the glove design or material.

### Protection limit :

Users should be warned that gloves should not be worn when there is a risk of entanglement by moving parts of machines.

This model does not contain any substances at levels that are known to, or suspected to, adversely affect user hygiene or health.

The protection against risks or hazards which are not mentioned in this document is not warranted.

The levels of performance mentioned are only valid for the palm of the glove.

The levels of performance mentioned are only valid for new gloves, not washed, nor regenerated.

These levels of performance are obtained from the tests done according to conditions defined by the applicable standards.

This glove shall not be in contact with fire

Contains natural rubber latex, which could cause allergic reaction, including anaphylactic choc.

Before use, the glove shall be visually controlled, in case of deterioration the gloves must be scrapped (abrasion, cut, tear, ...).

For gloves with different layers of material, the performance levels are warranted only for the whole glove.

For gloves with two or more layers the overall classification does not necessarily reflect the performance of the outermost layer.

### Storage and cleaning notice

Keep in its original packaging, under ordinary temperature and humidity conditions and in clean, covered and ventilated premises.

### PPE subject to ageing :

The design performance can not be significantly affect by ageing when stored in appropriate conditions (humidity, temperature, clean , ventilated, light).

### Declaration of conformity :

Available on : [www.handdier-safety.com](http://www.handdier-safety.com)