





Stainless steel wire in coil			
	Wire size mm	Coil weight, kg Approximately	Coil diameter, mm Approximately
	$0.20 \leq \phi \leq 0.3$	8-12	250-280
	$0.30 < \phi \leq 0.45$	15-25	280-310
	$0.45 < \phi \leq 0.65$	25-30	300-350
	$0.65 < \phi \leq 1.6$	45-50	400-450
	$1.6 < \phi \leq 5.0$	100-120	600-700

Carbon steel wire in coil			
	Wire size mm	Coil weight, kg Approximately	Coil diameter, mm Approximately
	$0.15 \leq d \leq 0.30$	15-20	250-300
	$0.30 < d \leq 0.45$	20-25	250-350
	$0.45 < d \leq 0.65$	25-30	300-350
	$0.7 < d \leq 1.3$	40-50	400-450
	$1.3 < d \leq 5.0$	100-120	560-650

Stainless steel wire in carrier for redrawing			
	Wire size mm	Coil weight, kg Approximately	Coil diameter, mm Approximately
	$1.0 \leq d \leq 1.6$	250-300	400-450
	$1.6 < d \leq 5.0$	350-400	600-700

Stainless steel wire in spool for spring						
	Type	130	160	200	250	355
	Flange	130	160	200	250	355
	External width	110	160	200	200	200
	Barrel	80	100	115	150	225
	Internal width	90	127	160	160	160
	Arbor hole	22	22	22	22	35
	Wire size range	0.080-0.180	0.100-0.250	0.100-0.280	0.150-0.350	0.200-0.600
	Weight of wire,kg	3	6	15	25	45